

VdS

# Smoke Alarm RM201



## Product ref.: 130756 Product features

- Optical scattered-light smoke alarm with Q-label certified according to EN 14604 and VdS 3131
- Maintenance-free thanks to battery life of up to 10 years
- Integrated emergency light illuminates the escape route in case of alarm
- Metal mesh around the smoke chamber offers protection against insects
- Easy installation with supplied screws and plugs
- Large and user-friendly push-button for functional tests and muting alarms
- Self-test and battery control function

#### **Technical specifications**

Supply voltage	permanently installed 3 V lithium battery	
Battery life	> 10 years (typ.)	
Degree of protection	IP20	
Ambient temperature	5 to 30 °C	
Alarm type	scattered-light smoke alarm	
Alarm output	Piezo signal device (>85 dB in 3 m distance), LED	
Display	Status LED	
Mark of conformity	CE, VdS, Q-label	
Dimensions (ø x H)	115 x 45 mm	
Weight	116 g (incl. battery)	

#### **Logistical data**

Product reference	130756
EAN code	4047976307562
Short description	RM201
Packing unit	32
Packing dimensions	146 x 65 x 180+30 mm
Total weight	281,6 g

### **Package contents**

Smoke alarm (incl. permanently installed 3 V lithium battery)	
Mounting material (screws and plugs)	
User manual in DE and EN	



