

Wireless Switch actuator 4-channel, surface-mount

Product ref.: 76796
PRODUCT FEATURES



- Jet-proof (IP65) and durable shutter actuator, ideal for use in outdoor areas or in locations which are prone to damp
- 4 independent switching channels
- Local operation directly on the device is supported
- Relay contact: Changeover switch (4x) floating
- Low current consumption
- Multiple remote controls can be connected
- Signal LED confirms that the radio signal has been received, for example
- Maximum ON time can be individually defined

TECHNICAL SPECIFICATIONS

Supply voltage:	230 V/50 Hz
Standby power consumption:	0.5 W
Degree of protection:	IP65
Relay:	4 changeover contacts (floating contacts)
Switching capacity:	16 A (resistive load)
Dimensions (W x H x D):	171 x 55 x 121 mm
Weight:	477.2 g
Radio frequency:	868.3 MHz
Typ. open area RF range:	300 m

LOGISTIC DATA

Product reference:	76796
EAN code:	4047976767960
Short description:	HM-LC-Sw4-SM
Packing unit:	12
Packaging dimensions:	184 x 281 x 97 mm
Total weight:	791.2 g

PACKAGE CONTENTS

Wireless Switch actuator 4-channel,
 surface-mount
 Operating manual in DE and EN