

BLUETOOTH® Smart Radiator Thermostat UK





- Radiator Thermostat with BLUETOOTH® smart for demand-based regulation of the room temperature via free iOS and Android smartphone app
- Operation also possible without smartphone at all times
- Configuration of the week program offers definition of individual temperature profiles with up to 7 switching times per day
- Boost function for heating up the radiator quickly and briefly
- Compact device with low-noise operation
- Via the app, up to 5 radiator thermostats can be combined and controlled in one room
- Management of up to 10 rooms via the app
- Up to 30 % energy savings within typical applications
- Automatic temperature reduction during ventilation saves additional energy
- Holiday function: The temperature can be reduced until you are back home
- Automatic frost protection: The room temperature does not fall below 5 °C
- Automatic protection against calcification by regular opening and closing of the valves
- Child-proof lock/operating lock prevents against unintended changes
- Fits to valves of most popular manufacturers
- Easy to mount without having to drain any water or intervene in the heating system; no special tools required, independent from the radiator type



Technical specifications

Supply voltage	2x 1.5 V LR6/Mignon/AA 2 years (typ.)	
Battery life		
Radio frequency	2.402 GHz – 2.480 GHz	
Smartphone operating systems	Supports iOS (version 8.3 and higher) and Android (version 4.4 and higher)	
Display	LC display	
Threaded connection	M30 x 1,5 mm (e.g. for Heimeier, MNG, Honeywell-Braukmann, Oventrop, Schlösser, Comap, Valf Sanayii, Idmar, Jaga, Junkers, Pegler, R.B.M., Watts, Danfoss RA, RA and RAVL with adapter)	
Dimensions (W x H x D)	58 x 63 x 122 mm	
Weight	176 g (including batteries)	

Logistical data

Product reference	142461D0
EAN code	4047976424627
Short description	CC-RT-M-BLE-EQ
Packing unit	60
Packing dimensions	109 x 70 x 126 +30 mm
Total weight	268 g

Package contents

www.eQ-3.com

BLUETOOTH® Smart Heizkörperthermostat Uk	(
Adapter for Danfoss valves (RA, RAV and RAVI	_)
Mounting material (support ring, nut M4, cylinder head screw M4 x 12 mm)	
2x 1.5 V LR6/mignon/AA batteries	
Operating manual in DE and EN	

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by eQ-3 AG is under license. Other trademarks and trade names are those of their respective owners.



