

Radiator Thermostat Model Q

Product ref.: 143478A0

Product features



- Radiator thermostat enables time-controlled regulation of the room temperature
- Smallest electronic radiator thermostat with integrated LC display
- Mounted without the need of tools and snap-on fastening on the valve
- Installation without having to drain any water or intervene in the heating system
- Comfortable operation and display at all times also in case of unfavourable installation conditions (e.g. in radiator niches)
- Low-noise gearbox offers installation of the device in sleeping rooms
- Can be universally used for valves from the most popular manufacturers
- Ready to use straight away thanks to preset heating profiles
- Setpoint temperature can be specified precisely (to the nearest 0,5°) via comfortable operation of the control wheel
- Can be individually tailored to personal routines – in the week program, variable temperatures for up to 6 heating phases (13 switching times) can be set separately
- Frost protection function against frost damage to the radiators
- Temperature fall detection for automatic reduction of the temperature during ventilation
- Smart descaling run for permanent protection against calcification
- Boost function for heating up the radiator quickly and briefly

Technical specifications

Supply voltage	2x 1.5 V LR6/mignon/AA
Battery life	3 years (typ.)
Degree of protection	IP20
Display	LC display
Threaded connection	M30 x 1,5 mm (e.g. for Heimeier, MNG, Honeywell-Braukmann, Oventrop, Schlösser, Comap, Valf Sanayii, Idmar, Jaga, Junkers, Pegler, R.B.M., Watts) as well as Danfoss RA, Danfoss RAV and Danfoss RAVL with corresponding adapter
Dimensions (W x H x D)	54 x 72 x 76 mm
Weight	147 g (including batteries)

Logistical data

Product reference	143478A0
EAN code	4047976434787
Short description	CC-RT-Q
Packing unit	60
Packing dimensions	80 x 68 x 123 mm
Total weight	153.5 g

Package contents

Radiator Thermostat Model Q
Adapter ring for M30 x 1.5 mm
Adapter for Danfoss RA, RAV and RAVL
Mounting material (nut M4, cylinder head screw M4 x 12 mm)
2x 1.5 V LR6/mignon/AA batteries
User manual in DE, EN, FR, NL