

Wired RS485 Shutter Actuator 1-channel, DIN rail mount



Product ref.: 76802
PRODUCT FEATURES



- Shutter actuator for standard DIN rail mounting in house- and sub-distribution boards
- Mounting width: 2 WM (35 mm)
- Circuit-breaker with two floating interlocked relay switching outputs for opening and closing e.g. shutters and awnings that have limit switches (mechanical or electronic) and 230 V AC motors
- As many floating buttons as are necessary can be connected to one button input
- Interference-proof thanks to bus cabling
- Easy programming at the device itself

TECHNICAL SPECIFICATIONS

Supply voltage:	24 VDC
Current consumption:	70 mA (max.)
Max. switching capacity:	230 V/50 Hz/4 A motor load
Degree of protection:	IP20
Ambient temperature:	0 to 35 °C
Dimensions (W x H x D):	35 x 87 x 64 mm (2 WM width)
Weight:	100 g
Communication:	RS485 bus

LOGISTIC DATA

Product reference:	76802
EAN code:	4047976768028
Short description:	HMW-LC-BI1-DR
Packing unit:	90
Packaging dimensions:	122 x 112 x 48 mm
Total weight:	176.2 g

PACKAGE CONTENTS

Homematic Wired RS485 Shutter Actuator
Operating manual in DE and EN