

Wireless LAN Gateway

Product ref.: 104029A0
PRODUCT FEATURES



- Extension of wireless range of a CCU2 in an installation - wireless interface of CCU2 remains activated
- Up to 3 LAN Gateways can be used within one installation with a CCU2 via the existing network infrastructure in the house
- Easy software update via CCU2
- Quick and easy integration of LAN Gateway into the network thanks to automatic address assignment via DHCP
- Increased operational reliability thanks to integrated recovery system
- Status displayed via three indicator lights

TECHNICAL SPECIFICATIONS

Supply voltage:	5 VDC
Current consumption:	250 mA max.
Standby power consumption:	0.8 W
Degree of protection:	IP20
Ambient temperature:	5 to 35 °C
Dimensions (W x H x D):	116 x 150 x 34 mm
Weight:	150 g (without power supply unit)
Radio frequency:	868.3 MHz
Typ. open area RF range:	500 m

LOGISTIC DATA

Product reference:	104029A0
EAN code:	4047976040292
Short description:	HM-LGW-O-TW-W-EU-2
Packing unit:	18
Packaging dimensions:	187 x 184 x 97 mm
Total weight:	497.0 g

PACKAGE CONTENTS

Wireless LAN Gateway
Plug-in mains adapter
Network cable
Mounting accessories (2x screws, 2x plugs)
Drilling template
Operating manual in DE and EN