

Wireless Rain Sensor

Product ref.: 130220
PRODUCT FEATURES



- Sensor immediately detects rain and snow
- Due to a low detection threshold and a large sensor area the device easily detects rain - switching commands are send immediately to connected Homematic devices
- An integrated sensor heating accelerates drying of the sensor area which prevents e.g. freezing or dew formation - unintended switching signals are being avoided
- Can be used for example in connection with a shutter actuator for automatic retraction of awnings in the event of rain or with a Homematic WinMatic to enable automatic closing of roof windows

TECHNICAL SPECIFICATIONS

Supply voltage:	7.5 - 30 VDC
Current consumption:	250 mA max.
Power consumption in standby:	0.4 W (without sensor heating)
Heating power sensor:	1 W
Degree of protection:	IP44
Ambient temperature:	-20 to +55 °C
Dimensions (W x H x D):	80 x 82 x 55 mm
Weight:	266 g
Radio frequency:	868.3 MHz
Typ. open area RF range:	200 m

LOGISTIC DATA

Product reference:	130220
EAN code:	4047976302208
Short description:	HM-Sen-RD-O
Packing unit:	32
Packaging dimensions:	184 x 140 x 73 mm
Total weight:	496.0 g

PACKAGE CONTENTS

Wireless Rain Sensor
Mounting accessories
Operating manual in DE and EN