

## Wireless Shutter Actuator 1-channel, surface-mount

Product ref.: 76800  
**PRODUCT FEATURES**



- Jet-proof (IP65) and durable shutter actuator, ideal for use in outdoor areas or in locations which are prone to damp.
- Allows the control of shutters or awnings
- Automatic retraction of awnings during strong winds in combination with a Homematic Wireless Weather Data Sensor
- In connection with a Central Control Unit: Adjustable movement times and direct positioning for movements
- Suitable for use with numerous standard shutter motors
- Operation via remote controls or directly on the device using connected push-buttons
- Low standby power consumption
- Signal LED confirms that the radio signal has been received, for example

### TECHNICAL SPECIFICATIONS

Power supply:	230 V / 50 Hz
Typ. open area RF range:	300 m
Radio frequency:	868.3 MHz
Relay contact:	1 NO contact, 1 changeover contact
Max. switching current:	800 W motor load
Standby consumption:	0.4 W
Degree of protection:	IP 65
Dimensions (W x H x D):	160 x 115 x 55 mm
Weight:	340 g

### LOGISTIC DATA

Product reference:	76800
EAN code:	4047976768004
Short description:	HM-LC-BI1-SM
Packing unit:	32
Packaging dimensions:	184 x 140 x 73 mm
Total weight:	475.0 g

### PACKAGE CONTENTS

Homematic Wireless Shutter Actuator 1-channel, flush-mount  
 Operating manual in DE and EN