

Wireless Smoke Alarm



Product ref.: 131408 PRODUCT FEATURES



- Optical scattered-light smoke alarm with VdS certification and Q label
- Maintenance-free thanks to battery life of up to 10 years
- Wireless Smoke Alarm based on Homematic wireless protocol and offering AES-128 security
- Up to 40 Homematic Wireless Smoke Alarms can be connected
- Emergency lighting by integrated LED during alarm
- Metal mesh around smoke chamber for protection against insects
- Easy installation with supplied screws and plugs
- Large and user-friendly push-button for functional tests and muting alarms
- Self-test and battery control function

Note: The device may only be operated in groups with smoke alarms of the same type (HM-Sec-SD-2, part-no. 131408) and not with other types of smoke alarms (e.g. HM-Sec-SD, part-no. 76676 and 83813).

TECHNICAL SPECIFICATIONS

Supply voltage:	Permanently installed 3 V lithium batteries
Battery life:	10 years (typ.)
Degree of protection:	IP20
Ambient temperature:	5 to 30 °C
Typ. open area RF range:	300 m
Radio frequency:	868.3 MHz
Alarm type:	Scattered-light wireless smoke alarm
Alarm output:	Piezo signal device (>85 dB in 3 m distance), status LED, radio
Display:	Duo status LED
Mark of conformity:	CE, VdS, Q-label
Dimensions (ø x H):	110 x 45 mm
Weight:	146 g (incl. batteries)

LOGISTIC DATA

Product reference:	131408
EAN code:	4047976314089
Short description:	HM-Sec-SD-2
Packing unit:	32
Packaging dimensions:	184 x 140 x 73 mm
Total weight:	325.0 g

PACKAGE CONTENTS

Wireless Smoke Alarm (incl. permanently installed 3 V lithium batteries)
Mounting material (screws and plugs)
Operating manual in DE and EN