

Wireless Switch Actuator 4-channel, DIN-rail mount

Product ref.: 91836
PRODUCT FEATURES



- Switches up to 4 connected loads
- For independent switching of components without an RS485 connection or an external antenna
- 4 inputs/outputs
- Can be configured and controlled wirelessly via the Homematic Central Control Unit CCU2
- Loads of up to 3680 W power consumption can be connected
- DIN-rail housing with width of 4 WM
- Device is equipped with operation/configuration button and display
- Low energy consumption

TECHNICAL SPECIFICATIONS

Supply voltage:	230 V/50 Hz
Current consumption:	20 mA
Power consumption in standby:	0.4 W
Maximum switching capacity:	3680 W (230 V/50 Hz/16 A per channel, total for all channels 25 A/5750 W max.)
Degree of protection:	IP20
Dimensions (W x H x D):	72 x 65 x 87 mm (standard DIN-rail housing with 4 WM width)
Weight:	189 g
Radio frequency:	868.3 MHz
Typ. open area RF range:	200 m

LOGISTIC DATA

Product reference:	91836
EAN code:	4047976918362
Short description:	HM-LC-Sw4-DR
Packing unit:	60
Packaging dimensions:	122 x 112 x 73 mm
Total weight:	269.0 g

PACKAGE CONTENTS

Wireless Switch Actuator 4-channel
 Operating manual in DE and EN