

Wireless Tilt Sensor

Product ref.: 83146
PRODUCT FEATURES



- Sensitive tilt sensor for precise determination of position deviations
- Ideal for monitoring garage doors, hatches, roof windows, containers and many other applications
- Detects deviations from the original position of a hatch, a garage door or a roof window
- Option of customising trigger point/angle of inclination setting
- Customisation to local conditions prevents false tripping caused by the wind or cars driving by
- Once the angle of inclination is changed, a switching command is triggered
- Compact, weather-proof housing (IP65) is suitable for outdoor applications
- Can be positioned anywhere as it runs on batteries, no wiring work required
- Long battery lifetime

TECHNICAL SPECIFICATIONS

Supply voltage:	1x lithium coin cell CR2032
Battery life:	3 years (typ.)
Degree of protection:	IP65
Dimensions (W x H x D):	50 x 50 x 35 mm
Weight:	55.6 g
Radio frequency:	868.3 MHz
Typ. open area RF range:	200 m

LOGISTIC DATA

Product reference:	83146
EAN code:	4047976831463
Short description:	HM-Sec-TiS
Packing unit:	90
Packaging dimensions:	122 x 112 x 48 mm
Total weight:	126.6 g

PACKAGE CONTENTS

Wireless Tilt Sensor
1x Lithium coin cell CR2032
Operating manual in DE and EN