

Pluggable Switch

Product ref.: 141836A0



Product features

- Enables switching of connected devices
- Within the Homematic IP climate control solution, the temperature of rooms with electric heaters can be precisely regulated in connection with the Homematic IP Wall Thermostat
- Within the Homematic IP security solution, the device automatically switches e.g. indoor sirens or alarm lights as soon as an alarm is triggered
- Easy installation: quickly and without any tools
- Manual operation: Connected devices can be switched on and off also directly on the device
- Low standby power consumption
- Thanks to the compact design, the pluggable switch does not block the surrounding sockets
- Comfortable and individual voice control (e.g. via Amazon Alexa or Google Assistant)
- For operation, the Homematic IP Access Point in connection with the Homematic IP app (no recurring costs), the Homematic Central Control Unit CCU2 or an appropriate partner solution is required

Technical specifications

Supply voltage	230 V/50 Hz
Current consumption	16 A (max.)
Standby power consumption	< 0.3 W
Max. switching capacity	3680 W
Load type	ohmic load
Degree of protection	IP20
Ambient temperature	-10 to +35 °C
Dimensions (W x H x D)	70 x 70 x 39 mm (not incl. mains plug)
Weight	154 g
Radio frequency	868.3 MHz/869.525 MHz
Typ. open area RF range	400 m

Logistical data

Product reference	141836
EAN code	4047976418367
Short description	HMIP-PS
Packing unit	45
Packing dimensions	122 x 112 x 97 mm
Weight incl. packaging	284.4 g

Package contents

Homematic IP Pluggable Switch

Operating manual