

# Wall-mount Remote Control - 2 buttons

Product ref.: 140665A0



## Product features

- Flexible wall-mount remote control with two channels for central control of Homematic IP devices
- At the touch of a button, e.g. the eco mode for all radiators or the panic alarm can be activated
- Can be flexibly mounted with supplied adhesive strips or screws
- Easy to integrate into existing switches from the following manufacturers: Berker (S.1, B.1, B.3, B.7 Glas), GIRA (System 55, Standard 55, E2, E22, Event, Esprit), Merten (1-M, Atelier-M, M-Smart, M-Arc, M-Star, M-Plan) JUNG (A 500, AS 500, A plus, A creation) and ELSO (Joy)

## Technical specifications

Supply voltage	2x 1.5 V LR03/micro/AAA
Current consumption	50 mA max.
Battery life	4 years (typ.)
Degree of protection	IP20
Ambient temperature	5 to 35 °C
Dimensions (W x H x D)	Without frame: 55 x 55 x 17 mm Incl. frame: 86 x 86 x 19 mm
Weight	82 g (incl. batteries)
Radio frequency	868.3 MHz/869.525 MHz
Typ. open area RF range	200 m

## Logistical data

Product reference	140665A0
EAN code	4047976406654
Short description	HMIP-WRC2
Packing unit	90
Packing dimensions	122 x 112 x 48 mm

## Package contents

Homematic IP Wall-mount Remote Control - 2 buttons

Clip-on frame

Mounting plate

Double-sided adhesive strips (2x)

Screws 3.0 x 30 mm (2x) and plugs 5 mm (2x)

1.5 V LR03/micro/AAA batteries (2x)

User manual