

Temperature and Humidity Sensor with Display – indoor

Product ref.: 150180A0



Product features

- Measuring of indoor temperature and humidity
- Shows the current temperature and humidity on a clear LC display
- Regulates the room temperature in connection with one or more Homematic IP Radiator Thermostats or Homematic IP Floor Heating Actuators
- Particularly user-friendly and immediately ready for use thanks to radio communication
- Simple and flexible installation thanks to supplied adhesive strips or screws
- Integration into multi-gang frames or 55 mm frames of other manufacturers (Berker, ELSO, Gira, merten, JUNG)
- Can be used with the Home Control Access Point in connection with the Homematic IP app, the Homematic Central Control Unit CCU2 as well as with various partner solutions

Technical specifications

Supply voltage	2x 1.5 V LR03/micro/AAA
Current consumption	20 mA max.
Battery life	2 years (typ.)
Degree of protection	IP20
Ambient temperature	5 to 35 °C
Dimensions (W x H x D)	Without frame: 55 x 55 x 23.5 mm Incl. frame: 86 x 86 x 25 mm
Weight	65 g (including batteries)
Radio frequency	868.3 MHz/869.525 MHz
Typ. open area RF range	180 m

Logistical data

Product reference	150180A0
EAN code	4047976501809
Short description	HmIP-STHD
Packing unit	90
Packing dimensions	122 x 112 x 48 mm

Package contents

Homematic IP Temperature and Humidity Sensor with display – indoor
Clip-on frame
Mounting plate
Double-sided adhesive strips (2x)
Screws 3.0 x 30 mm (2x) and plugs 5 mm (2x)
1.5 V LR03/micro/AAA batteries (2x)
User manual