

Window / Door Contact – invisible installation

Product ref.: 151039A0



Product features

- Reliably detects open and closed windows and doors by an integrated infra-red light barrier
- Invisible installation on the inside of plastic window or door frames and easy mounting using adhesive strips
- The inconspicuous device is not visible if the window or door is closed
- For installation, a minimum distance of 15 mm between frame and casement is required
- The room temperature is reduced automatically during ventilation in connection with a Homematic IP Radiator Thermostat
- On request, an alarm is triggered e.g. in combination with the Homematic IP Siren as soon as a window or door is opened
- Open windows and doors are directly displayed in the Homematic IP app – the current status can be requested at any time even while being away from home
- The built-in tamper contact informs via the app about any manipulation of the window / door contact
- Can be used with the Access Point in connection with the Homematic IP app (no recurring costs), the Homematic Central Control Unit CCU2 as well as with various partner solutions

Technical specifications

| | |
|-------------------------|-------------------------------------|
| Supply voltage | 2x 1.5 V LR03/micro/AAA |
| Current consumption | 50 mA max. |
| Battery life | 5 years (typ.) |
| Degree of protection | IP20 |
| Dimensions (W x H x D) | 166.5 x 12.5 x 19 mm |
| Weight | 47 g (including batteries) |
| Radio frequency band | 868.0-868.6 MHz 869.4-868.65 MHz |
| Typ. open area RF range | 230 m |

Logistical data

| | |
|--------------------|------------------|
| Product reference | 151039A0 |
| EAN code | 4047976510399 |
| Short description | HmIP-SWDO-I |
| Packing unit | 72 |
| Packing dimensions | 184 x 93 x 48 mm |

Package contents

Homematic IP Window / Door Contact – invisible installation

Double-sided adhesive strips (2x)

Reflecting sticker (for dark surfaces)

1.5 V LR03/micro/AAA batteries (2x)

User manual