

# Water Sensor

Product ref.: 151694A0



## Product features

- Reliably detects humidity on different surfaces as well as a water level from 1.5 mm height
- Arising humidity and water are indicated via the integrated siren of the water sensor or, if available, via the Homematic IP Alarm Siren as well as the Homematic IP App
- With an integrated tilt sensor, unintended movement or manipulation of the water sensor is detected and indicated immediately
- Flexible adaptation to the installation site thanks to battery operation and spring-mounted measuring probes
- Individual adjustment of triggering behaviour via the Homematic IP app
- For operation, the Homematic IP Access Point in connection with the Homematic IP app (no recurring costs), the Homematic Central Control Unit CCU2 or an appropriate partner solution is required



## Technical specifications

Supply voltage	2x 1,5 V LR03/micro/AAA
Current consumption	100 mA max.
Battery life	5 years (typ.)
Degree of protection	IP44
Ambient temperature	-20 to +55 °C
Dimensions (W x H x D)	80 x 80 x 30 mm
Weight	78.2 g (including batteries)
Radio frequency band	868.0-868.6 MHz 869.4-869.65 MHz
Typ. open area RF range	230 m
Volume integrated siren	approx. 77 dB (in a distance of 1 m)

## Logistical data

Product reference	151694A0
EAN code	4047976516940
Short description	HmIP-SWD
Packing unit	90
Packing dimensions	122 x 112 x 48 mm
Weight incl. packaging	154.2 g

## Package contents

- Homematic IP Water Sensor
- 1.5 V LR03/micro/AAA batteries (2x)
- User manual