

# Radiator Thermostat (UK)

Product ref.: 151038A0



## Product features

- Replaces conventional thermostats and controls the radiator according to the individual needs of the user
- Up to three adjustable week profiles: The room temperature can be adjusted according to individually tailored heating phases (up to 6 per day with configurable temperature)
- The temperature can automatically be reduced during ventilation thanks to the open-window function or in combination with the Homematic IP Window / Door Contact
- Secure installation: Thanks to the metal nut and supplied adapters, the device can be securely fixed to various standard radiators
- Easy installation: no need to drain water or to intervene into the heating system
- Manual operation: Temperature changes and activating the boost function (heating up the radiator quickly) can be performed directly on the device
- Comfortable and individual voice control (e.g. via Amazon Alexa or Google Assistant)
- For operation, the Homematic IP Access Point in connection with the Homematic IP app (no recurring costs), the Homematic Central Control Unit CCU2 or an appropriate partner solution is required

## Technical specifications

Supply voltage	2x 1.5 V LR6/mignon/AA
Current consumption	120 mA (max.)
Battery life	2 years (typ.)
Degree of protection	IP20
Ambient temperature	0 to 50 °C
Dimensions (W x H x D)	58 x 71 x 97 mm
Weight	205 g (incl. batteries)
Radio frequency band	868.0-868.6 MHz 869.4-869.65 MHz
Typ. open area RF range	300 m
Connection	M30 x 1.5 mm

## Logistical data

Product reference	151038A0
EAN code	4047976510382
Short description	HmIP-eTRV-2-UK
Packing unit	45
Packing dimensions	122 x 112 x 97 mm
Weight incl. packaging	333.0 g

## Package contents

Homematic IP Radiator Thermostat (UK)

Adapters Danfoss (RA, RAV and RAVL)

Danfoss RAV spigot extension

Support ring

Cylinder head screw M4 x 12 mm and nut M4

1.5 V LR6/mignon/AA batteries (2x)

User manual