

# **Radiator Thermostat Model L**



## Product ref.: 130809G0 Product features

- Radiator thermostat enables time-controlled regulation of room temperature
- Timeless, simple housing and compact design
- Easy to mount without having to drain any water or intervene in the heating system; no special tools required
- Suitable for universal use; compatible with the products of the most popular valve manufacturers
- Ready to use straight away thanks to preset programming
- Setpoint temperature can be specified precisely and intuitive (to the nearest 0,5 °) via adjustment wheel
- Can be individually tailored to personal routines in the week program, for each weekday up to 3 heating phases (7 change settings) can be set separately
- Automatic frost protection and temperature fall detection
- Valve protection function: Automatic protection against calcification thanks to regular opening and closing of valves
- Boost function for heating up the radiator quickly and briefly
- Tamper-proof thanks to child-proof lock/operating lock

Supply voltage	2x 1.5 V LR6/mignon/AA 3 years (typ.) - 3 heating cycles	
Battery life		
Degree of protection	IP20	
Display	LCD	
Threaded connection	M30 x 1.5 mm (e.g. for Heimeier, MNG, Honeywell-Braukmann, Oventrop, Schlösse Comap, Valf Sanayii, Idmar, Jaga, Junkers, Pegler, R.B.M., Watts, Danfoss RA, RAV ar RAVL with adapter)	
Dimensions (W x H x D)	58 x 71.5 x 90 mm	
Weight	126.5 g	

### **Technical specifications**

#### **Logistical data**

Product reference	130809G0
EAN code	4047976318094
Short description	CC-RT-O-CnL-W-R5-2-EQ
Packing unit	30
Packing dimensions	85 x 80 x 110+30 mm
Total weight	252,1 g

#### **Package contents**

Radiator Thermostat Model L	
3 adapters for Danfoss valves (RA, RAV and RAVL)	
Mounting material (support ring, nut M4, cylinder head screw M4 x 12 mm)	
2x 1.5 V LR6/mignon/AA batteries	
User manual in DE, EN, FR and NL	

