

Radiator Thermostat Model N



Product ref.: 132231K0 Product features

- Radiator thermostat enables time-controlled regulation of room temperature
- Timeless, simple housing and compact design
- Low-noise gearbox
- Easy operation thanks to inclined arrangement of buttons and display even if the device is difficult to access
- Easy to mount without having to drain any water or intervene in the heating system; no special tools required
- Suitable for universal use; compatible with the products of the most popular valve manufacturers
- Ready to use straight away thanks to preset programming
- Setpoint temperature can be specified precisely and intuitive (to the nearest 0,5 °) via adjustment wheel
- Can be individually tailored to personal routines in the week program, for each weekday up to 3 heating phases (7 change settings) can be set separately
- Automatic frost protection and temperature fall detection
- Valve protection function: Automatic protection against calcification thanks to regular opening and closing of valves
- Boost function for heating up the radiator quickly and briefly
- Tamper-proof thanks to child-proof lock/operating lock

Supply voltage	2x 1.5 V LR6/mignon/AA			
Battery life	3 years (typ.) - 3 heating cycles			
Degree of protection IP20				
Display	LCD			
Threaded connection	M30 x 1.5 mm (e.g. for Heimeier, MNG, Honeywell-Braukmann, Oventrop, Schlösser, Comap, Valf Sanayii, Idmar, Jaga, Junkers, Pegler, R.B.M., Watts, Danfoss RA with adapter)			
Dimensions (W x H x D)	55 x 60 x 102 mm			
Weight	160 g (incl. battery)			

Technical specifications

Logistical data

Product reference	132231K0		
EAN code	4047976132225		
Short description	CC-RT-N-EQ		
Packing unit	75		
Packing dimensions	69 x 66 x 111+30 mm		
Total weight	217.4 g		

Package contents

Adapter	for Danfos	s valves	(RA)		
	ng material head screv		-	M4,	
2x 1.5 V	LR6/migno	on/AA ba	tteries		

User manual in DE, EN, FR and PL

