

## Central Control Unit CCU2

**Product ref.: 103584**  
**PRODUCT FEATURES**



- Homematic Central Control Unit is the central element of your Homematic system, offering a whole range of control, monitoring and configuration options for all the Homematic devices in your installation
- Comfortable operation via PC or tablet with the Homematic user interface WebUI
- Enables the configuration and operation as well as querying of status information of all Homematic devices
- Complex control tasks and individual logic functions can be realised via Central Control Unit programs
- Easy replacement of devices
- Easy replacement of Central Control Unit
- WebUI available in German and English
- Internal memory can be expanded using the microSD card slot, e.g. for third-party applications
- Firmware of Homematic devices can be updated via the WebUI user interface
- Direct links between Homematic devices remain active even without the involvement of the Central Control Unit

### TECHNICAL SPECIFICATIONS

Supply voltage:	5 VDC (plug-in mains adapter)
Input:	100 - 240 VAC, 50/60 Hz, 0.5 A
Output:	5 VDC, 1500 mA
Ambient temperature:	5 to +35 °C
Degree of protection:	IP20
Dimensions (W x H x D):	116 x 150 x 34 mm
Weight:	165 g
Radio frequency:	868.3 MHz
Typ. open area RF range:	400 m

### LOGISTIC DATA

Product reference:	103584
EAN code:	4047976035847
Short description:	HM-Cen-O-TW-x-x-2
Packing unit:	18
Packaging dimensions:	187 x 184 x 97 mm
Total weight:	599.0 g

### PACKAGE CONTENTS

Homematic Central Control Unit CCU2
Plug-in mains adapter
Mounting accessories (2x screws, 2x plugs)
USB cable
LAN cable
Drilling template
Operating manual in DE and EN