

## Remote Control 4 buttons, alarm



Product ref.: 130466A0  
**PRODUCT FEATURES**



- Remote control with four buttons for controlling the alarm functions of your CCU2 and to switch lights on and off
- Via the WebUI user interface, you can connect the remote control with other Homematic devices, such as motion detectors or window sensors and individually configure alarm functions via CCU programs ("if-then-connections")
- Space-optimised design enables use of AAA batteries
- Batteries can be replaced easily without tools
- Haptic perception of buttons
- Glass fibre reinforced and halogen-free material offers optimal stability and environmental compatibility
- Secure operation thanks to AES authentication and direct feedback during wireless communication via duo colour LED
- Convenient key ring supplied

### TECHNICAL SPECIFICATIONS

|                          |   |
|--------------------------|---|
| Supply voltage:          | 1x 1.5 V LR03/micro/AAA                               |
| Current consumption:     | 100 mA max.   |
| Battery life:            | > 3 years (based on a usage rate of 10 times per day) |
| Degree of protection:    | IP20  |
| Ambient temperature:     | -10 to +55 °C   |
| Dimensions (W x H x D):  | 38 x 75 x 14 mm                                       |
| Weight:                  | 38 g (incl. batteries)                                |
| Radio frequency:         | 868.3 MHz   |
| Typ. open area RF range: | 200 m   |

### LOGISTIC DATA

|                       |                  |
|-----------------------|------------------|
| Product reference:    | 130466A0         |
| EAN code:             | 4047976404667    |
| Short description:    | HM-RC-Sec4-3     |
| Packing unit:         | 144              |
| Packaging dimensions: | 122 x 93 x 36 mm |
| Total weight:         | 98 g             |

### PACKAGE CONTENTS

|   |
|---|
| Homematic Remote Control 4 buttons, alarm |
| Key ring                                  |
| 1.5 V LR03/micro/AAA battery              |
| Operating manual in DE and EN             |