

Wired RS485 LAN Gateway, DIN rail mount

Product ref.: 103755
PRODUCT FEATURES



- LAN Gateway for standard DIN rail mounting in house- and sub-distribution boards
- Mounting width: 2 WM (35 mm)
- Enables communication between Homematic Wired devices and the Homematic Central Control Unit CCU2 via the existing network structure in the house. No additional bus lines are required
- Communication to connected Homematic devices is established via the Homematic Wired protocol
- After teaching-in the Homematic RS485 LAN Gateway to the Homematic Central Control Unit, the Wired system can be flexibly controlled from everywhere in the house

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|------------------------------|
| Supply voltage: | 24 VDC/SELV |
| Current consumption: | 100 mA (max.) |
| Standby power consumption: | 0.75 W |
| Degree of protection: | IP20 |
| Ambient temperature: | 0 to 35 °C |
| Dimensions (W x H x D): | 35 x 87 x 64 mm (2 WM width) |
| Weight: | 76 g |
| Communication: | RS485 bus |
| Network: | Ethernet, 10/100Base-T |

LOGISTIC DATA

| | |
|-----------------------|--------------------|
| Product reference: | 103755 |
| EAN code: | 4047976037551 |
| Short description: | HMW-LGW-O-DR-GS-EU |
| Packing unit: | 90 |
| Packaging dimensions: | 122 x 112 x 48 mm |
| Total weight: | 163.9 g |

PACKAGE CONTENTS

| |
|-----------------------------------|
| Homematic Wired RS485 LAN Gateway |
| Ethernet cable |
| Operating manual in DE and EN |