

Wired RS485 Switch Actuator 2-channel, DIN rail mount



Product ref.: 76801
PRODUCT FEATURES



- Circuit-breaker with two independent floating relay switching outputs for standard DIN rail mounting in house- and sub-distribution boards
- Mounting width: 2 WM (35 mm)
- Both switching channels can be programmed separately
- Load per channel in 230 V power supply of up to 16 A
- All outputs are electrically isolated from the inputs
- As many floating buttons as are necessary can be connected to one button input
- Interference-proof thanks to bus cabling
- Easy programming at the device itself

TECHNICAL SPECIFICATIONS

Supply voltage:	24 VDC
Current consumption:	70 mA (max.)
Max. switching capacity:	230 V/50 Hz/16 A (per relay), total for all channels max. 25 A
Degree of protection:	IP20
Ambient temperature:	0 to 35 °C
Dimensions (W x H x D):	35 x 87 x 64 mm (2 WM width)
Weight:	99 g
Communication:	RS485 bus

LOGISTIC DATA

Product reference:	76801
EAN code:	4047976768011
Short description:	HMW-LC-Sw2-DR
Packing unit:	90
Packaging dimensions:	122 x 112 x 48 mm
Total weight:	175.0 g

PACKAGE CONTENTS

Homematic Wired RS485 Switch Actuator
Operating manual in DE and EN