

Wireless Dimming Actuator 2-channel, trailing edge, surface mount

Product ref.: 85972
PRODUCT FEATURES



- The surface-mount dimming actuator allows dimming of incandescent lamps, HV and LV halogen lamps (with electronic transformer) and dimmable energy-saving lamps as well as dimmable LEDs
- Jet-proof (IP65), suitable for outdoor application
- Low quiescent current draw saves electricity
- Operation directly on the device, e.g. for installation check
- Automatic soft-start for longer bulb life
- Easy installation with concealed fastening tabs
- Several Homematic transmitters can be connected to one dimming actuator
- Signal LED confirms that the radio signal has been received, for example

TECHNICAL SPECIFICATIONS

Supply voltage:	230 V/50 Hz
Current consumption:	30 mA
Power consumption in standby:	1 W
Effective installed load:	2x 300 VA
Degree of protection:	IP65
Dimensions (W x H x D):	171 x 55 x 121 mm (not incl. heat sink)
Weight:	264 g
Radio frequency:	868.3 MHz
Typ. open area RF range:	300 m

LOGISTIC DATA

Product reference:	85972
EAN code:	4047976859726
Short description:	HM-LC-Dim2T-SM
Packing unit:	18
Packaging dimensions:	187 x 184 x 97 mm
Total weight:	659 g

PACKAGE CONTENTS

Wireless Dimming Actuator 2-channel
 Operating manual in DE and EN