

Wireless Door/Window Sensor, optical



Product ref.: 130297
PRODUCT FEATURES



- Wireless door/window sensor for optical recognition of open and closed doors and windows
- Compact design and integrated infra-red sensor (reflection coupler) - there is no need of an additional magnet contact
- Due to the supplied white and brown caps the device adapts to door and window frames
- Simple and flexible installation thanks to supplied adhesive stripes or screws
- Integration tamper contact informs about unauthorised removal and manipulation
- Secure thanks to AES authentication

TECHNICAL SPECIFICATIONS

Supply voltage:	1x 1.5 V LR03/micro/AAA
Current consumption:	100 mA max.
Battery life:	2 years (typ.)
Degree of protection:	IP20
Ambient temperature:	-20 to +55 °C
Dimensions (W x H x D):	15 x 100 x 18 mm
Weight:	30 g
Radio frequency:	868.3 MHz
Typ. open area RF range:	300 m

LOGISTIC DATA

Product reference:	130297
EAN code:	4047976302970
Short description:	HM-Sec-SCo
Packing unit:	144
Packaging dimensions:	122 x 93 x 36 mm
Total weight:	99.6 g

PACKAGE CONTENTS

Wireless Door/Window Sensor, optical
 1.5 V LR03/micro/AAA
 2x Covers
 Double-sided adhesive strips
 2x Countersunk head screws 2.2 x 13 mm
 Reflecting sticker
 Operating manual in DE and EN