

Wireless Switch Actuator 1-channel, plug adapter type J



Product ref.: 141130A0
PRODUCT FEATURES



- Wireless switch actuator enables switching of connected loads via radio
- Can be easily mounted without tools - after the device has been plugged in, it is immediately ready for use
- Easy operation - directly on the device or via the WebUI of the Central Control Unit CCU2
- Multiple remote controls can be taught-in
- Low current consumption
- Current switching status of device is indicated by device LED
- Switch on and off delay as well as switch on and switch off duration can be individually adjusted
- Rugged design: $\cos\phi=1$: 40,000 switching cycles

TECHNICAL SPECIFICATIONS

Supply voltage:	230 V/50 Hz
Current consumption:	10 A (max.)
Power consumption in standby:	< 0.6 W
Degree of protection:	IP20
Ambient temperature:	-10 to +35 °C
Radio frequency:	868.3 MHz
Typ. open area RF range:	300 m
Max. switching capacity:	2300 W
Load type:	ohmic load
Relay:	NO contact, 1-pole, μ contact
Dimensions (W x H x D):	59 x 122 x 40 mm (not incl. mains plug)
Weight:	162 g

LOGISTIC DATA

Product reference:	141130A0
EAN code:	4047976411306
Short description:	HM-LC-Sw1-PI-DN-R5
Packing unit:	32
Packaging dimensions:	184 x 140 x 73 mm
Total weight:	350 g

PACKAGE CONTENTS

1x Wireless Switch Actuator type J
1x Operating manual in DE, EN, FR and IT