

Alarm Siren

Product ref.: 142801A0



Product features

- Audible and visual signal output in alarm cases via piezo speaker and LEDs
- Early warning thanks to loud acoustic signal with ≥ 90 dB @ 1 m distance as well red signal LEDs
- Optional acoustic signals for activating or deactivating the security solution
- Different acoustic signals and the alarm duration can be defined
- Tamper contact detects manipulation or unauthorised removal
- Easy and flexible wall or ceiling mounting out of reach for burglars using supplied screws and plugs
- Design similar to smoke alarm
- To enable operation, the device has to be connected with one of the following solutions:
 - Homematic IP Access Point with free smartphone app and free cloud service
 - Central Control Unit CCU2/CCU3 with the local user interface WebUI
 - Third-party solutions of partners

Technical specifications

Supply voltage	3x 1.5 V LR6/mignon/AA
Battery life	2 years (typ.)
Degree of protection	IP20
Ambient temperature	5 to 35 °C
Dimensions (ø x H)	124 x 45 mm
Weight	136 g (including batteries)
Radio frequency band	868.0-868.6 MHz 869.4-869.65 MHz
Typ. open area RF range	250 m

Logistical data

Product reference	142801A0
EAN code	4047976428014
Short description	HmlIP-ASIR
Packing unit	32
Packing dimensions	184 x 140 x 73 mm
Weight incl. packaging	345.4 g

Package contents

Homematic IP Alarm Siren

Ceiling bracket

1,5 V LR6/mignon/AA batteries (3x)

Mounting material (screws (2x) and plugs (2x))

User manual