og/2020 Smart Home Information security tested Homematic IP www.VDEinfo.com ID. 40046786

Starter Set Water Alarm

Product ref.: 153405A0



Technical specifications (per device)

Access Point:		
Supply voltage	power supply unit (5 VDC)	
Dimensions (W x H x D)	118 x 104 x 26 mm	
Typical open area RF range	400 m	

Water Sensor:

Supply voltage	2x 1.5 V LR03/micro/AAA	
Battery life	5 years (typ.)	
Degree of protection	IP44	
Ambient temperature	-20 to +55 °C	
Dimensions (W x H x D)	80 x 80 x 30 mm	
Typical open area RF range	230 m	
Volume integrated siren	approx. 77 dB (at a distance of 1 meter)	

Alarm siren:

Supply voltage	3x 1.5 V LR6/mignon/AA	
Battery life	2 years (typ.)	
Dimensions (ø x H)	124 x 45 mm	
Typical open area RF range	250 m	

For further technical details and information please refer to the data sheet of the respective device

Logistical data

Product reference	153405A0
EAN code	4047976534050
Short description	HmIP-SK8
Packing unit	6
Packing dimensions	325 x 159 x 106 mm
Weight incl. packaging	1127.8 g



Product features

- Reliable monitoring and alarming in case of humidity and water in your own four walls
- The Access Point connects your smartphone via the Homematic IP cloud with all Homematic IP devices
- The water sensor triggers an alarm in case of humidity or a water level higher than 1.5 mm - ideal for monitoring of bathrooms or cellars
- The alarm siren offers additional acoustic and visual signalling in case of alarm
- An alarm is triggered in case of humidity and water via the integrated siren of the water sensor or via the alarm siren as well as the Homematic IP app
- Highly reliable Homematic IP radio protocol based on 868 MHz
- High security thanks to comprehensive AES encryption and server location in Germany – no personal data required
- The starter set water alarm can be expanded into a comprehensive smart home system at any time together with various different Homematic IP devices

Package contents