



Product features

- Interface between MAX! wireless components and home network
- Flexible heating control at any place via MAX! smartphone apps (Android, iOS) or via the MAX! portal with any Internet connection
- Quick and easy local configuration of all MAX! components via the MAX! software
- Increased security thanks to encrypted, authenticated communication within the network (AES-128) as well as authenticated bidirectional wireless communication with all components
- Easy to install and use without any need of network know-how: no configuration of router or firewall required
- All individual device settings and parameters are stored locally so the system can even be operated independently of a PC or active Internet connection
- Comfortable control of up to 50 devices in max. 10 rooms
- Three LEDs for operational status display

Technical specifications

Supply voltage:	Input: 100-240 V~/350 mA Output: 5 V=/550 mA
Power consumption in standby:	1.1 W
Degree of protection:	IP20
Dimensions (W x H x D):	80 x 80 x 80 mm
Weight:	130 g
Radio frequency:	868.3 MHz
Typ. open area RF range:	> 100 m
Connection:	RJ-45 (Ethernet)

Logistical data

Product reference:	99004
EAN code:	4047976990047
Short description:	BC-LGW-0-TW
Packing unit:	30
Packing dimensions:	122 x 112 x 147 mm
Total weight:	460 g

Package contents

1x MAX! Cube LAN Gateway
1x Plug-in USB power supply
1x USB cable
1x Network cable
1x Mounting accessories
1x Assembly bracket for wall mounting
1x Operating manual in DE/EN (further languages on request)