



Product features

- Ideal solution for starting to use the MAX! system: In the MAX! Radiator solution immediately ready for use to control single radiators - even without Internet connection
- Can be individually tailored to personal routines thanks to the freely programmable heating phases (13 switching times per day for temperature switch-over) directly on the radiator thermostat
- Simple expansion to MAX! Room or House solution
- Easy installation without having to intervene in the heating system; no special tools required
- Ready to use straight away thanks to pre-set week programs
- Precise temperature adjustment (to the nearest 0.5°C)
- Automatic temperature reduction when the windows are opened for ventilation and adjustment of the temperature when they are closed in connection with MAX! Window Sensors
- Frost protection function automatically opens valves if necessary
- Limescale protection automatically protects against calcification thanks to regular opening and closing of the valves
- Boost button for heating up the radiator immediately
- Tamper-proof thanks to child-proof lock/operating lock
- Theft protection available as an option

Technical specifications

Supply voltage:	2x 1.5 V LR06/mignon/AA batteries
Current consumption:	100 mA max.
Battery life:	2 years (typ.)
Display:	LC display (backlit)
Threaded connection:	M30 x 1.5 mm
Dimensions (W x H x D):	60 x 65 x 100 mm
Weight:	216 g (incl. batteries)
Radio frequency:	868.3 MHz
Typ. open area RF range:	> 100 m

Logistical data

Product reference:	105936
EAN code:	4047976059362
Short description:	BC-RT-TRX-CyG-4
Packing unit:	45
Packing dimensions:	122 x 112 x 97 mm
Total weight:	372.0 g

Package contents

1x MAX! Radiator Thermostat+
2x LR06/mignon/AA batteries
3x Adapters for Danfoss valves (RA, RAV, RAVL)
1x Plunger extension (for RAV)
1x Cylinder head screw M4 x 12 mm
1x Nut M4
1x Support ring
1x Operating manual in DE/EN (further languages on request)